



OPEN TOP ROLL-OFF CONTAINER

Specifications

Meets or exceeds ANSI Z245.30 - 1996

MODEL	A HEIGHT INSIDE	B HEIGHT OUTSIDE	C WIDTH OVERALL	D LENGTH OVERALL
10 yd.	42 in.	52 in.	96 in.	12 ft. 9 in.
15 yd.	42 in.	52 in.	96 in.	16 ft. 9 in.
20 yd.	42 in.	52 in.	96 in.	22 ft. 9 in.
30 yd.	62 in.	72 in.	96 in.	22 ft. 9 in.
40 yd.	84 in.	94 in.	96 in.	22 ft. 9 in.

UNDERSTRUCTURE	3" CHANNEL
CROSSMEMBERS	16" APART
RUNNERS	2" x 6" x 1/4" TUBING
SOLID BULL NOSE	1-1/4" PLATE - BURNOUT
FLOOR	3/16" OR 1/4" PLATE
PUSH PLATE	26" x 16" x 3/16"
CABLE HOOK	1-1/4" PLATE - BURNOUT
HOOKE PLATE	23" x 15" x 3/4"
WHEELS	8" x 10" REAR, 8" x 6" FRONT (OPTIONAL)
WHEEL AXLES	1-1/2" ROUND BAR
FRONT NOSE ROLLERS	4" DIAMETER x 6" WIDE
UPPER WALL CONSTRUCTION	12, 10 OR 7 GAUGE
TOP RAILS	3" x 4" x 7 GA. TUBING
SIDE POSTS	5" x 3" FORMED ON 2' CENTERS
REAR CORNER POST	3-1/2" x 7" x 3/16"
TAILGATE FRAME	3" x 4" x 7 GA. TUBING & FORMED DIRT SHEDDER HORIZONTAL POSTS
TAILGATE LATCH SYSTEM	UP LIFT
HINGES	3 - 8" x 2" w/ 1-1/4" PIN (2-20 YARD)
PAINTED	ONE SOLID COLOR WITH RUST-INHIBITIVE PAINT
INTERIOR	FULL WELD CONSTRUCTION
CONSPICUITY	ANSI APPROVED TRAFFIC REFLECTORS
OPTIONAL HOOK-UP AVAILABLE	HOOK-LIFT SYSTEMS, HEIL, DINO

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE